

Size 3A "21x21"	3p + ⊕ - Screw terminal inserts	4p + ⊕ - Screw terminal inserts
S-A Series  US (UL, CSA) 10 A 230/400V 4kV 3 Working current Working voltage conductor-ground Working voltage conductor-conductor Rated impulse voltage Pollution degree	  Wire section / AWG 0,5 - 1,5 mm² / AWG 20-16 Numbering 1 - 3 + ⊕ Part number 7203.6001.0 Female 7203.6101.0 Male	  Wire section / AWG 0,5 - 1,5 mm² / AWG 20-16 Numbering 1 - 4 + ⊕ Part number 7204.6002.0 Female 7204.6102.0 Male
Size 10A "49x16"	10p + ⊕ - Screw terminal inserts	10p + ⊕ - Inserts for crimp contacts
S-A Series  US (UL, CSA pending) 16 A 250V 4kV 3 Working current Working voltage Rated impulse voltage Pollution degree <i>Please order crimp contacts separately, page 16</i>	  Wire section / AWG 0,5 - 2,5 mm² / AWG 20-14 Numbering 1 - 10 + ⊕ Part number 7210.4401.0 Female 7210.4401.0 Male	  Wire section / AWG 0,14 - 4 mm² / AWG 26-12 Numbering 1 - 10 + ⊕ Part number 7210.4451.0 Female 7210.4461.0 Male
Size 16A "66x16"	16p + ⊕ - Screw terminal inserts	16p + ⊕ - Inserts for crimp contacts
S-A Series  US (UL, CSA pending) 16 A 250V 4kV 3 Working current Working voltage Rated impulse voltage Pollution degree <i>Please order crimp contacts separately, page 16</i>	  Wire section / AWG 0,5 - 2,5 mm² / AWG 20-14 Numbering 1 - 16 + ⊕ Part number 7216.4402.0 Female 7216.4412.0 Male	  Wire section / AWG 0,14 - 4 mm² / AWG 26-12 Numbering 1 - 16 + ⊕ Part number 7216.4452.0 Female 7216.4462.0 Male
Size 32A "66x40"	32p + ⊕ - Screw terminal inserts	32p + ⊕ - Inserts for crimp contacts
S-A Series  US (UL, CSA pending) 16 A 250V 4kV 3 Working current Working voltage Rated impulse voltage Pollution degree <i>Please order crimp contacts separately, page 16</i>	  Wire section / AWG 0,5 - 2,5 mm² / AWG 20-14 Numbering 1 - 16 + ⊕ / 17-32 + ⊕ Part number 7216.4402.0 F 7216.4403.0 7216.4412.0 M 7216.4413.0	  Wire section / AWG 0,14 - 4 mm² / AWG 26-12 Numbering 1 - 16 + ⊕ / 17-32 + ⊕ Part number 7216.4452.0 F 7216.4453.0 7216.4462.0 M 7216.4463.0